



[mail@movitbrakes.com](mailto:mail@movitbrakes.com)  
[movitbrakes.com](http://movitbrakes.com)

	Front Axle										Rear Axle						Comments					
	304x32	322x32	342x34	342x34	370x35	370x35	380x32	380x32	396x36	436x38	460x38	299x24	322x28	322x32	342x28	370x35		370x35	380x32	396x36	460x38	
	4k	4K	4K	6KB	4K	6KB	4K	6K	6KB	6KB	6KB	4K	4K	4K	4K	4K		6K	4K	6K	6K	
<b>Jaguar</b>																						
X-Type (06.01-)		21 006	21 106																			322 / 4s3 needs 13 mm SV with Nothelle 8.5x19" rims 322 / 4s3 needs 13 mm SV with Nothelle 8.5x19" rims
XJ Typ XJ 40, 81 (10.86-11.94)			21 108																			
XJ 6 / 12 (10.69 - 12.92)			21 108																			
XJS Coupé (09.75 - 03.96)			21 108																			
XJ Typ X300 (11.94 - 07.97)		21 003	21 108										21 004									
XJ Typ NAW, NBW (07.97 - )		21 003	21 101										21 004									required for original 18" wheels 5 mm SV
XK8, XKR Convertible Typ QEV (03.96 - )		21 003	21 101										21 004									required for original 18 " wheels 5 mm SV
XK8, XJR Coupé Typ QDV (03.96 - )		21 003	21 101										21 004									required for original 18" wheels 5 mm SV